



500 Kw Cummins Diesel Generator 625kv Sia Ktaa19-G6a Engine Lent Dg Set

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO
- Model Number: DE-CC690S
- Minimum Order Quantity: 1pc
- Price: USD30000-50000/PC
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 30 DAYS
- Supply Ability: 1 MONTH 500PCS



Product Specification

- Rated Voltage: 400/230V, 220V / 380V, 110V / 240V, 380V
- Speed: 1500/1800rpm
- Frequency: 50/60HZ
- Rated Current: Depend
- Rated Power: 5KVA - 2000KVA
- Output Type: AC Three Phase
- Warranty: 12 Months/1000 Hours
- Alternator: Stamford, Leroy Somer, Dellent Factory Made
- Type: Silent(super Silent) or Open
- Product Name: Diesel Generator, Powered By Cummins Diesel Generator
- Name: 500 Kw Cummins Diesel Generator
- Engine: Powered By Cummins
- Control Panel: Deepsea, ComAp, Smartgen
- Controller: Smartgen, Deepsea, ComAp, Deepsea/Smartgen/etc

for more products please visit us on dellentpower.com

Product Description

Ce Cummins 500 Kw Diesel Generator 625kv Sia Ktaa19-G6a Engine Lent Dg Set

Our Product Introduction

for more products please visit us on dellentpower.com

50 Hz

60 Hz

TECHNICAL DATA

CUMMINS

DCEC Series Diesel Generator Sets

	Genset Performance				Engine Performance							Dimension(L×W×H)			
	Genset Model		Prime Power		Standby Power		Engine model	Speed	Prime power	Fuel Cons. (100% Load)	Cylinder-Bore×Stroke	Displacement	Open Type	Silent Type	
	kW	kVA	kW	kVA		rpm	kW	L/h	Qty./mm	L	cm	cm			
50Hz	DE-C22	16	20	17.6	22	4B3.9-G11	1500	20	5.3	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C30	22	27.5	24	30	4B3.9-G1/G2	1500	27	7.1	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C34	25	31	27.5	34	4B3.9-G12	1500	27	7.4	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C44	32	40	35	44	4BT3.9-G1	1500	36	10	4L-102×120	3.9	168×84×125	230×102×150		
	DE-C44	32	40	35	44	4BT3.9-G2	1500	36	9.3	4L-102×120	3.9	168×84×125	230×102×150		
	DE-C55	40	50	44	55	4BTA3.9-G2	1500	50	11.2	4L-102×120	3.9	175×90×125	230×102×150		
	DE-C66	48	60	52.8	66	4BTA3.9-G2	1500	50	14.1	4L-102×120	3.9	183×90×125	230×102×150		
	DE-C90	64	80	72	90	4BTA3.9-G11	1500	70	17.6	4L-102×120	3.9	187×90×125	240×102×150		
	DE-C94	68	85	75	94	6BT5.9-G1	1500	86	18.6	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C94	68	85	75	94	6BT5.9-G2	1500	86	19	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C100	72	90	80	100	6BT5.9-G1	1500	86	20.5	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C100	72	90	80	100	6BT5.9-G2	1500	86	22	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C110	80	100	88	110	6BT5.9-G1	1500	86	24.5	6L-102×120	5.9	220×100×140	272×108×152		
	DE-C110	80	100	88	110	6BT5.9-G2	1500	86	24	6L-102×120	5.9	220×100×140	272×108×152		
	DE-C125	90	113	100	125	6BTA5.9-G2	1500	106	27	6L-102×120	5.9	220×100×140	272×108×152		
	DE-C150	108	135	120	150	6BTA5.9-G2	1500	120	30	6L-102×120	5.9	230×100×140	290×108×157		
	DE-C165	120	150	132	165	6BTA5.9-G12	1500	140	32.5	6L-102×120	5.9	240×100×140	300×108×157		
	DE-C175	128	160	140	175	6BTA5.9-G12	1500	140	34	6L-102×120	5.9	240×100×140	300×108×157		
	DE-C200	144	180	160	200	6CTA8.3-G1	1500	163	42	6L-114×135	8.3	242×100×150	320×110×177		
	DE-C200	144	180	160	200	6CTA8.3-G2	1500	163	42	6L-114×135	8.3	242×100×150	320×110×177		
DE-C220	160	200	176	220	6CTA8.3-G2	1500	183	45	6L-114×135	8.3	248×100×156	350×120×185			
DE-C275	200	250	220	275	6LTA8.9-G2	1500	220	53	6L-114×145	8.9	262×100×164	360×120×185			
DE-C303	220	275	242	303	6LTA9.5-G3	1500	250	58	6L-114×145	9.5	267×100×164	370×120×185			
DE-C344	250	313	275	344	6LTA9.5-G1	1500	290	70	6L-114×145	9.5	267×110×164	370×130×185			
DE-C413	300	375	330	412.5	6ZTAA13-G3	1500	340	76.5	6L-130×163	13	300×138×200	441×173×223			
DE-C440	320	400	352	440	6ZTAA13-G2	1500	390	89	6L-130×163	13	300×138×200	441×173×223			
DE-C500	360	450	400	500	QSZ13-G2	1500	400	70.4	6L-130×163	13	320×138×200	461×173×223			
DE-C550	400	500	440	550	QSZ13-G3	1500	450	101	6L-130×163	13	320×138×200	461×173×223			
60Hz	DE-C28	20	25	22	27.5	4B3.9-G11	1800	23	7.1	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C38.5	28	35	31	38.5	4B3.9-G12	1800	33	9.4	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C45	33	41	36	45	4BT3.9-G2	1800	40	9.6	4L-102×120	3.9	162×84×125	230×102×150		
	DE-C55	40	50	44	55	4BT3.9-G2	1800	40	10.3	4L-102×120	3.9	168×84×125	230×102×150		
	DE-C69	50	62.5	55	69	4BTA3.9-G2	1800	60	13.5	4L-102×120	3.9	175×90×125	230×102×150		
	DE-C75	54	67.5	60	75	4BTA3.9-G2	1800	60	15.5	4L-102×120	3.9	183×90×125	230×102×150		
	DE-C100	72	90	80	100	4BTA3.9-G11	1800	80	20.1	4L-102×120	3.9	187×90×125	240×102×150		
	DE-C107.5	78	97.5	86	107.5	6BT5.9-G2	1800	100	23.5	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C125	90	112.5	100	125	6BT5.9-G2	1800	100	29	6L-102×120	5.9	220×90×140	272×108×152		
	DE-C143	104	130	114	143	6BTA5.9-G2	1800	120	27.8	6L-102×120	5.9	220×100×140	272×108×152		
	DE-C163	120	150	130	163	6BTA5.9-G2	1800	132	34	6L-102×120	5.9	230×100×140	290×108×157		
	DE-C175	128	160	140	175	6BTA5.9-G12	1800	150	38	6L-102×120	5.9	240×100×140	300×108×157		
	DE-C200	144	180	160	200	6CTA8.3-G2	1800	170	44	6L-114×135	8.3	242×100×150	320×110×177		
	DE-C250	182	227	200	250	6CTA8.3-G2	1800	190	49	6L-114×135	8.3	248×100×156	350×120×185		
	DE-C275	200	250	220	275	6LTA8.9-G2	1800	235	59	6L-114×145	8.9	262×100×164	360×120×185		
	DE-C300	220	275	240	300	6LTA8.9-G3	1800	255	63	6L-114×145	8.9	262×100×164	360×120×185		
	DE-C330	240	300	264	330	6LTA9.5-G1	1800	265	65	6L-114×145	9.5	267×100×164	370×120×185		
	DE-C344	250	313	275	344	6LTA9.5-G1	1800	280	68	6L-114×145	9.5	267×110×164	370×130×185		
	DE-C413	300	375	330	412.5	6ZTAA13-G3	1800	340	81	6L-130×163	13	300×138×200	441×173×223		
	DE-C440	320	400	352	440	6ZTAA13-G2	1800	390	89	6L-130×163	13	300×138×200	441×173×223		
DE-C500	360	450	400	500	QSZ13-G2	1800	408	73.6	6L-130×163	13	300×138×200	441×173×223			
DE-C550	400	500	440	550	QSZ13-G3	1800	450	101	6L-130×163	13	300×138×200	441×173×223			

50 Hz 60 Hz

TECHNICAL DATA

CUMMINS

CCEC Series Diesel Generator Sets

50Hz	Genset Performance				Engine Performance						Dimension(L×W×H)		
	Prime Power		Standby Power		Engine model	Speed	Prime power	Fuel Cons. (100% Load)	Cylinder-Bore×Stroke	Displacement	Open Type	Silent Type	
	kW	kVA	kW	kVA									rpm
	DE-CC275	200	250	220	275	MTA11-G2	1500	224	59	6-125×147	10.8	280×110×167	400×140×203
	DE-CC275	200	250	220	275	NT855-GA	1500	231	53.4	6-140×152	14	303×112×190	420×140×213
	DE-CC300	220	275	240	300	NTA855-G1A	1500	261	61.3	6-140×152	14	313×112×190	420×140×213
	DE-CC350	250	312.5	280	350	MTAA11-G3	1500	282	61.3	6-125×147	10.8	313×112×190	420×140×213
	DE-CC350	250	312.5	280	350	NTA855-G1B	1500	284	71.4	6-140×152	14	313×112×190	420×140×213
	DE-CC375	275	344	300	375	NTA855-G2A	1500	312	71.9	6-140×152	14	322×112×190	420×140×213
	DE-CC412	300	375	330	412.5	NTAA855-G7	1500	343	85.4	6-140×152	14	329×122×190	450×140×213
	DE-CC450	320	400	360	450	NTAA855-G7A	1500	369	89.2	6-140×152	14	325×122×190	450×140×213
	DE-CC500	360	450	400	500	KTA19-G3	1500	403	97	6-159×159	18.9	337×140×217	480×170×220
	DE-CC550	400	500	440	550	KTA19-G3A	1500	448	107	6-159×159	18.9	337×140×217	480×170×220
	DE-CC550	400	500	440	550	KTA19-G4	1500	448	107	6-159×159	18.9	337×140×217	480×170×220
	DE-CC575	420	525	460	575	KTAA19-G5	1500	470	113	6-159×159	18.9	347×152×220	500×190×223
	DE-CC650	460	575	520	650	KTA19-G8	1500	522	125	6-159×159	18.9	344×140×217	450×140×213
	DE-CC690	500	625	550	690	KTAA19-G6A	1500	555	138	6-159×159	18.9	354×152×220	500×190×223
	DE-CC712	520	650	570	712	QSK19-G4	1500	574	143	6-159×159	19	354×152×220	500×190×223
	DE-CC800	580	725	640	800	KT38-GA	1500	647	165	12-159×159	37.8	432×196×247	620×228×256
	DE-CC825	600	750	660	825	KTA38-G2	1500	664	167	12-159×159	37.8	432×196×247	620×228×256
	DE-CC880	640	800	704	880	KTA38-G2B	1500	711	170	12-159×159	37.8	432×196×247	620×228×256
	DE-CC1000	728	910	800	1000	KTA38-G2A	1500	813	191	12-159×159	37.8	432×196×247	680×228×256
	DE-CC1100	800	1000	880	1100	KTA38-G5	1500	881	209	12-159×159	37.8	440×208×254	680×228×256
	DE-CC1250	900	1125	1000	1250	KTA38-G9	1500	991	236	12-159×159	37.8	450×208×254	680×228×256
	DE-CC1375	1000	1250	1100	1375	KTA50-G3	1500	1097	261	16-159×159	50.3	493×208×253	40 feet high container
	DE-CC1512	1100	1375	1210	1512	KTA50-G8	1500	1200	289	16-159×159	50.3	497×220×253	
	DE-CC1650	1200	1500	1320	1650	KTA50-GS8	1500	1287	309	16-159×159	50.3	497×220×253	
60Hz	DE-CC275	200	250	220	275	NT855-GA	1800	234	59.4	6-140×152	14	303×112×190	420×140×213
	DE-CC325	240	300	260	325	NTA855-G1	1800	287	73.4	6-140×152	14	313×112×190	420×140×213
	DE-CC375	275	344	300	375	NTA855-G1B	1800	313	80	6-140×152	14	313×112×190	420×140×213
	DE-CC440	315	394	350	440	NTA855-G3	1800	358	87	6-140×152	14	313×112×190	420×140×213
	DE-CC500	350	437.5	400	500	KTA19-G2	1800	392	98	6-159×159	18.9	337×140×217	480×170×220
	DE-CC563	410	512.5	450	562.5	KTA19-G3	1800	463	111	6-159×159	18.9	337×140×217	480×170×220
	DE-CC625	450	562.5	500	625	KTA19-G3A	1800	507	120	6-159×159	18.9	337×140×217	480×170×220
	DE-CC688	470	587.5	550	687.5	KTAA19-G5	1800	533	134	6-159×159	18.9	347×152×220	500×190×223
	DE-CC750	540	675	600	750	KTAA19-G6A	1800	604	155	6-159×159	18.9	354×152×220	500×190×223
	DE-CC750	550	687.5	600	750	QSK19-G5	1800	608	155	6-159×159	19	354×152×220	500×190×223
	DE-CC850	620	775	680	850	KT38-G	1800	679	154	12-159×159	37.8	432×196×247	620×228×256
	DE-CC1000	725	906	800	1000	KTA38-G2	1800	809	204	12-159×159	37.8	432×196×247	620×228×256
	DE-CC1100	800	1000	880	1100	KTA38-G2A	1800	915	225	12-159×159	37.8	432×196×247	680×228×256
	DE-CC1250	900	1125	1000	1250	KTA38-G4	1800	1007	245	12-159×159	37.8	440×208×254	680×228×256
	DE-CC1375	1000	1250	1100	1375	KTA38-G9	1800	1109	261	12-159×159	37.8	450×208×254	680×228×256
	DE-CC1562	1100	1375	1250	1562	KTA50-G3	1800	1220	291	16-159×159	50.3	493×208×253	40 feet high container
	DE-CC1875	1260	1575	1500	1875	KTA50-G9	1800	1384	330	16-159×159	50.3	497×220×253	



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY,NINGDE CITY,FUJIAN.CHINA