

CHINA

DELLENT

CE/ISO9001

DE-SC110

face to face

500 PCS PER MONTH

## Standby Power SDEC Diesel Generator 110kva Soundproof Engine With 4 Cylinder In Line

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1\*20GP
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



## **Product Specification**

• Name:

• Frequency:

Engine Brand:No. Of Cylinder:

• Rated Speed:

Voltage:Warranty:

• Controller:

• Highlight:

Prime Power:

Standby Power:

• Engine Model:

SDEC Diesel Generator 110kva 4HTAA4.3-G21 50Hz SDEC 4 Cylinder In Line 1500rpm 400V/230V 12 Months Smartgen 80kW/100kVA 88kW/110kVA

PLASTIC WRAP OR PLYWOOD CASE

30 DAYS FROM DEPOSIT RECEIVED

Standby Power SDEC Diesel Generator, SDEC Diesel Generator 110kva, 110kva Diesel Generator

**Our Product Introduction** 

# 110kva Standby Power SDEC Genset Soundproof Engine By 4 Cylinder In Line

**110kva Standby Power SDEC Genset Soundproof Engine By 4 Cylinder In Line** Dellent Power supply the standby power 110kVA water cooled diesel generator with SDEC brand diesel engine model 4HTAA4.3-G21. The water cooled diesel generator with rated output 100kVA / 80kW, standby power110kVA / 88kW.



### 110kVA Diesel Generator Powered by SDEC Diesel Engine:

Model		DE-SC110
Max. Power	kVA	110.0
	kW	88.0
Rate Power	kVA	100.0
	kW	80.0
Frequency	Hz	50
Rate Voltage	V	400/230
Rate Current	A	144.3
SDEC Diesel Engine:	1	L
Engine Specification		

Engine Specification			
Engine Manufacturer		Shanghai Diesel Engine Co., Ltd.	
Engine Brand	SDEC		
Engine Model		4HTAA4.3-G21	
No. of Cylinder		4 Cylinder in line	
Aspiration		Turbocharged and Aftercooled	
Governor		Electric	
Engine Max. Output Power	kW	105	
Displacement	L	4.300	
Starting Voltage	V	24	

Bore	mm		105		
Stroke	mm	124			
Lubrication Oil Capacity	L	11-13			
Compression Ratio		16 : 1			
Intake Air Flow	M3/Min	6.8			
Fuel Consumption at 100% Load	L/H	23.0			
Specification of Control Panel:					
Control Panel Specification					
Controller Brand		Smartgen			
Breaker Brand		Delixi			
Breaker Capacity	A	125			
Battery Charger		Smartgen Model BAC06A			
Emergency Stop Button		Supply			
Automatic Mains Fail (AMF)		Supply			
Fuel Level		Supply			
Automatic Transfer Switch		ATS as optional part			
Mains Monitor		Supply with DELLENT Function			
The control panel supply the full protectio include Start-up fault (generator set shutc set shutdown), Low oil pressure (alarm an cooling fluid level alarm (as optional), Ove voltage high (alarm).	down), High ( nd generator	coolan <sup>.</sup> set sł	t temperature (alarm and generator nutdown), Low fuel level (alarm), Low		
Optional controller: Each model of Deeps	ea, Smartge	en, Cor	mAp brand controller.		
		Why	Choose Us:		
Dedica We are DEDICATED to m		ers' n	eed.		
	-				

Enthusiasm We respond to our Customers' ENTHUSIASM

We cherish our Customers' LOYALTY







We adopt NEWEST technologies for products

rust We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:



FAQ

Q: What's your delivery time?

A: Standard product 20 days - 35 days. Customized product 40 days.

Q: Can we add our logo to products?

A: Yes, there are several ways to do this. We can put the label of your logo on the products or make the silk print of your logo on the products. It is free.

Q: Can we customize the product?

A: We have a very experienced technical team, we can customize any product according to your requirements, such as synchronization system, wet exhaust system, ultra-silent system

