

6HTAA6.5-G22 SDEC Diesel Generator 150kVA Open Type Genset

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1*20GP

CHINA

DELLENT

CE/ISO9001

DE-SC165

face to face

500 PCS PER MONTH

- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

• Name:

• Frequency:

• Engine Brand:

Engine Model:

SDEC Diesel Generator Open Type 6HTAA6.5-G22 50Hz SDEC 6 Cylinder In Line

PLASTIC WRAP OR PLYWOOD CASE

30 DAYS FROM DEPOSIT RECEIVED

- No. Of Cylinder: 6 Cylinder In Li
- Rated Speed:
- Voltage:
- Warranty:
- Controller:
- Prime Power:
- Standby Power:
- Highlight:
- 1500rpm 400V/230V 12 Months Deepsea/Smartgen/ ComAp
- 120kW/150kVA
- 132kW/165kVA
 - SDEC Diesel Generator 150kVA, SDEC Diesel Generator Open Type, 150kVA Open Type Genset

Our Product Introduction

6HTAA6.5-G22 SDEC Diesel Engine 150kVA Open Type Genset

. PRODUCT DESCRIPTION

150kVA Standby Power SDEC Genset Soundproof Engine By 6 Cylinder In Line. Dellent Power supply the standby power 150kVA water cooled diesel generator with SDEC brand diesel engine model6HTAA6.5-G22. The water cooled diesel generator with rated output 165kVA /132kW, standby power150kVA /120kW.

1. Diesel generators are strong-built, ideal for emergency back-up,job sites and industrial appplications.

2. Powered by reliable air/water cooled diesel generators sets, industrial grade, great fuel efficiency, less maintenance, long operating life.

3. Strong technology and high-quality personnel, continuous innovation and perfect management.



150kVA Diesel Generator Powered by SDEC Diesel Engine:

Model		DE-SC165
Max. Power	kVA	165.0
	kW	132.0
Rate Power	kVA	150.0
	kW	120.0
Frequency	Hz	50
Rate Voltage	V	400/230
Rate Current	A	216.5

Specification of the Diesel Engine:

Engine Manufacturer		Shanghai Diesel Engine Co., Ltd.
Engine Brand		SDEC
Engine Model		6HTAA6.5-G22
No. of Cylinder		6 Cylinder in line
Aspiration		Turbocharged and Air to Air Aftercooled
Governor		Electric
Engine Max. Output Power	kW	155
Displacement	L	6.500
Starting Voltage	V	24
Bore	mm	105
Stroke	mm	124
Lubrication Oil Capacity	L	15-17.5
Compression Ratio		16 : 1
Intake Air Flow	M ³ /Min	N.A
I		1

Fuel Consumption at 100% Load	L	33.1
-------------------------------	---	------

Specification of Automatic Control Panel:

Controller Brand	Deepsea		
Controller Model	DSE6120		
Breaker Brand	Delixi		
Breaker Capacity	A 250		
Battery Charger	Smartgen Model BAC06A		
Emergency Stop Button	Supply		
Automatic Mains Fail (AMF)	Supply		
Fuel Level	Supply		
Automatic Transfer Switch	ATS as optional part		
Mains Monitor	Supply with DELLENT Function		

The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).

Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.



We are DEDICATED to meet Customers' need.

г 61 We respond to our Customers' ENTHUSIASM



We cherish our Customers' LOYALTY

We aim to establish our own LUXURY brand





We adopt NEWEST technologies for products



We strive for winning the TRUST from Customers



CERTIFICATE







「夏安葆電社



▲ 授权书



候权州





. QUALIFICATION CENTIFICATE:







NO.7, JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY, NINGDECITY, FUJIAN. CHINA