

CHINA

CE ISO DE-P88

1PC

face to face PLASTIC WRAP

30 DAYS

DELLENT-PERKINS

500 PCS PER MONTH

Standby Power Perkins Diesel Generator 450kVA 50Hz 2206C-E13TAG3

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

Name:Brand:

Cooling System:

Frequency:Alternator:

• Engine Model:

• Prime Power:

• Highlight:

• Standby Power:

• Phase:

Type:Controller:

Perkins Diesel Generator 450kVA Perkins Water Cooling 50HZ Alternator Three Phase Diesel Generator Smartgen DSE 2206C-E13TAG3 320kVA/400kW 360kVA/450kW Standby Power Perkins Diesel Generator, Perkins Diesel Generator 450kVA,

Perkins 2206C-E13TAG3

High Light:

Commercial Perkins 450kVA Generator, 2206C-E13TAG3 Engine Diesel Generator, CE Perkins 450kva Generator, 50HZ

.PRODUCT DESCRIPTION

2206C-E13TAG3 50Hz 450kVA Standby Power Perkins Diesel Generator Set

Product Introduce:Dellent Power Perkins Series generator powered by the original Perkins engine, it enjoys high stability, reliability, durability, and long life with a wide range of power output. It is widely used in the area of the port, railway, industrial, and mining.





Product parameters:

	DE-P450
kVA	450
kW	360
kVA	400
kW	320
Hz	50
V	400/230
A	577.4
L	600
mm	3500 X 1200 X 1960
kg	3480
mm	4350 X 1450 X 2180
kg	5260
^t dBA	80
•	Two of Free Maintenance Battery
	kW kVA kW Hz V A L L kg mm kg

Engine Specification:

Engine Manufacturer		Perkins Engines Company Limited	
Engine Brand		Perkins	
Engine Model		2206C-E13TAG3	
No. of Cylinder		6 Cylinder in line	
Aspiration		Turbocharged and Air to Air Aftercooled	
Governor		Electric	
Engine Max. Output Power	kW	413	
Displacement	L	12.5	

Compression Ratio		16.3 : 1		
Starting Voltage	V	24		
Bore	mm	130		
Stroke	mm	157		
Lubrication Oil Capacity	L	38		
Intake Air Flow	M3/Min	12.5		
Fuel Consumption at 100% Load	L/H	85		
Specification of Control Panel: Control Panel Specification				
Controller Brand		Smartgen		
Breaker Brand		Delixi		
Breaker Capacity (A)		630		
Emergency Stop Button		Supply		
Automatic Mains Fail (AMF)		Supply		
Fuel Level		Supply		
Automatic Transfer Switch		ATS as optional part		

The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).

Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.





NO.7, JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY, NINGDECITY, FUJIAN.CHINA