

CHINA

DELLENT

CE/ISO9001

DE-SC633

face to face

## SDEC Diesel Generator 50hz 450kVA Rated Power Generator Set

#### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1\*20GP
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



### **Product Specification**

Name:Frequency:

SDEC Diesel Generator Set 50Hz SDEC

6 Cylinder L Ttyp

1500rpm

500kVA

400V/230V 12 Months

SC25G690D2

500 PCS PER MONTH

PLASTIC WRAP OR PLYWOOD CASE

30 DAYS FROM DEPOSIT RECEIVED

- No. Of Cylinder:
- Rated Speed:

• Engine Brand:

- Voltage:
- Warranty:
- Engine Model:
- Prime Power: 450kVA
- Standby Power:

**Our Product Introduction** 

# SDEC Diesel Generator 50hz 450kVA Rated Power Generator Set

. PRODUCT DESCRIPTION

SDEC Diesel Generator 50hz 450kVA Rated Power Generator Set



#### Specification:

Model		DE-SC633
Max. Power	kVA	500
	kW	400
Rate Power	kVA	450
	kW	360
Frequency	Hz	50
Rate Voltage	V	400/230
Rate Current	А	811.9
Specification of the Diesel Engine	e:	
Engine Manufacturer		Shanghai Diesel Engine Co., Ltd.
Engine Brand		SDEC
Engine Model		6KTAA25-G35
No. of Cylinder		6 Cylinder L Ttyp
Aspiration		Turbocharged & Aftercooled
Governor		ECU
Engine Max. Output Power	kW	572
Displacement	L	25.8
Compression Ratio		16:01
Starting Voltage	V	24
Bore	mm	170
Stroke	mm	185
Lubrication Oil Capacity	L	76
Intake Air Flow	L/S	N.A.



Our company is located in Fu'an, which is known as the City of Motors. Our company was established in 2001. We have a deep manufacturing foundation and good quality guarantee.Compared with other factories, we have this differents: Firstly, for the silent shell of the unit, we use 2mm cold-rolled plates, while other factories mainly use 1.8mm hot-rolled plates. Secondly, we use 2.5mm hot-rolled plate for the chassis fuel tank.Thirdly,the hinges, door locks and some standard parts are all made of 304 stainless steel and will not rust and our factory has a special production line for plastic spraying, so you don't have to worry about uneven spraying.

